

Technical data sheet

M-iClean UM

Execution for: Afghanistan

Glasswasher

Alternating current: 1N PE 230V 50Hz

Fresh water line: Soft cold water 0-3 °dH



Sample illustration

Technical data

Rack capacity/h (theoretical)	20 / 20 / 15 racks/h
Programme cycle time	180 / 180 / 240 s
Rack dimension	500 x 500 mm
Entry height	315 mm
Dimensions (W x Hmin x D)	600 x 700 x 600 mm
Electrical feeding cable	Alternating current 1N PE 230V 50Hz* Total connected load: 2,9 kW max. rated current: 15,7 A
Local fuse protection	16 A
Protection class of the machine	IP X5
Equipment	Control system MIKE CPU4 Bluetooth interface for wireless communication Leakage detector Boiler safety device Automatic self-cleaning when tank is drained
Fresh water line	Air gap 'AB' in accordance with EN 1717 with booster pump
Fresh water supply	Minimum flow pressure 60 kPa / 0,6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5,0 bar Max. supply water temperature 60 °C
Flow rate	3 l/min
Final rinse water quantity	2,4 liters/cycle, variable
Boiler	Contents: 7,9 l Heater: 2,00 kW Temperature: 65 °C Tank / boiler locked
Wash tank	Filling: 11,0 l Heater: 2,00 kW Temperature: 60 °C

Technical data sheet

Wash pump, with frequency converter	Performance: 0,50 kW
Dosing of rinse aid	Hose pump (24 V) with time control and suction lance
Detergent dosage	Hose pump (24 V) with time control and suction lance
Material	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4571
Heat emission	for 20 programme cycles/h total: 2,1 kW perceptible: 1,4 kW latent: 0,7 kW
Ventilation flow rate	540 m ³ /h
Steam emission	1,0 kg/h
Emission sound pressure level at the workplace (LpA)	60 dB
Net / gross weight	63,0 kg / 74,8 kg (standard packaging)
Packaging dimensions (W x H x D)	700 x 1050 x 700 mm (standard packaging)

*Note:

Electrical equipment suitable for supply voltage:
3N PE 400 V 50 HZ (3N PE 380-415 V 50 Hz)
1N PE 230 V 50 HZ (1N PE 220-240 V 50 Hz)